

Safety Data Sheet



according to OSHA Hazard Communication
29 CFR Part 1910.1200

Section 1. Identification

Product Information: 22W-E008

Product Name: GORILLA® WHITE ACRYLIC ZONE MARKING PAINT

Recommended Use: Liquid Paint

Application Method: See Product Data Sheet

Supplied by: Aexcel Corporation
7373 Production Drive.
Mentor, OH 44060

Emergency Telephone: Chemtrec: 800-424-9300

Safety Data Sheet Coordinator: IWebb@AexcelCorp.com

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor.

GHS Classification

Asp. Tox. 1, Eye Irrit. 2A, Flam. Liq. 2, Repr. 2, Skin Irrit. 2, STOT RE 2, STOT SE 3 NE

Symbol(s) of Product



Signal Word

Danger

Possible Hazards

46% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Aspiration Hazard, category 1	H304	May be fatal if swallowed and enters airways.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Flammable Liquid, category 2	H225	Highly flammable liquid and vapour.
Reproductive Toxicity, category 2	H361	Suspected of damaging fertility or the unborn child.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
STOT, single exposure, category 3, NE	H336	May cause drowsiness or dizziness.
Skin Irritation, category 2	H315	Causes skin irritation.

GHS LABEL PRECAUTIONARY STATEMENTS

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.

P280	Wear protective gloves/protective clothing/eye protection/face protection.
P281	Use personal protective equipment as required.
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P302+P352	IF ON SKIN: Wash with plenty of water.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a POISON CENTER/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P331	Do NOT induce vomiting.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local rules and regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P363	Wash contaminated clothing before reuse.

Section 3. Composition/Information on ingredients

<u>Chemical Name</u>	<u>CAS-No.</u>	<u>Wt. %</u>	<u>GHS Symbols</u>	<u>GHS Statements</u>
TOLUENE	108-88-3	25-50	GHS07-GHS08	H304-315-319-336-361-373
TITANIUM DIOXIDE	13463-67-7	10-25	GHS06-GHS08	H331-361
ACETONE	67-64-1	2.5-10	GHS07	H320-335-336

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures

FIRST AID - INHALATION: Move to fresh air in case of accidental inhalation of vapors or decomposition products. Move to fresh air. Oxygen or artificial respiration if needed.

FIRST AID - SKIN CONTACT: If skin irritation persists, call a physician. Wash off immediately with soap and plenty of water. Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

FIRST AID - EYE CONTACT: Rinse with plenty of water.

FIRST AID - INGESTION: Consult a physician. Do not induce vomiting without medical advice. Never give anything by mouth to an unconscious person.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

SPECIAL FIREFIGHTING PROCEDURES: Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 7. Handling and storage



HANDLING: Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

STORAGE: Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH-TLV STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>
TOLUENE	20 ppm	NE	200 ppm	300 ppm
TITANIUM DIOXIDE	N.E.	N.E.	N.E.	N.E.
ACETONE	500 ppm	750 ppm	1000 ppm	NE

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation
Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.



HYGIENIC PRACTICES: Contaminated work clothing should not be allowed out of the workplace. General industrial hygiene practice. Keep working clothes separately.

Section 9. Physical and Chemical Properties

Boiling Range:	133 - 485	Vapor Density:	3.10
Odor:	Characteristic	Odor Threshold:	NE
Appearance:	Heavy Liquid	Evaporation Rate:	14.40
Solubility in Water:	NE	Specific Gravity:	1.294
Freeze Point:	NE	pH:	NE
Vapor Pressure:	226.00	Viscosity:	NE
Physical State:	Liquid	Flash Point, °C:	-17, °F 1.4

(See section 16 for abbreviation legend)

<u>CHEMICAL NAME</u>	<u>VAPOR DENSITY</u>	<u>EVAPORATION RATE</u>	<u>BOILING POINT</u>	<u>VP mmHg</u>	<u>at DEG. F</u>
TOLUENE	3.10	2.00	231	16.70	68
TITANIUM DIOXIDE	NE	NE	0	NE	NE
ACETONE	2.00	14.40	133	226.00	68

Section 10. Stability and reactivity

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist.

INCOMPATIBILITY: Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed.

CARCINOGENICITY: No Information

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

<u>CAS-No.</u>	<u>Name according to EEC</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
108-88-3	TOLUENE	5580	12196	12500
13463-67-7	TITANIUM DIOXIDE	10000	10000	6.80
67-64-1	ACETONE	N.I.	N.I.	N.I.

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

Section 13. Disposal considerations



Product

DISPOSAL METHOD: Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

DOT Proper Shipping Paint, Flammable Liquid

DOT Technical Name: Paint

DOT Hazard Class: 3

DOT UN/NA Number: 1263

Packing Group: II

Hazard SubClass: No Information

Resp. Guide Page: 128

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Reproductive toxicity, Skin Corrosion or Irritation, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard

SARA SECTION 312:

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3
ACETONE	67-64-1

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3

TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
BUTYL METHACRYLATE COPOLYMER	28262-63-7
CALCIUM CARBONATE	1317-65-3

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
BUTYL METHACRYLATE COPOLYMER	28262-63-7
CALCIUM CARBONATE	1317-65-3
WOLLASTONITE (CALCIUM METASILICATE)	13983-17-0
HYDRATED MAGNESIUM SILICATE	14807-96-6

CALIFORNIA PROPOSITION 65 CARCINOGENS**WARNING**

The following ingredients present in the product are known to the state of California to cause Cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
TITANIUM DIOXIDE	13463-67-7

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

<u>Chemical Name</u>	<u>CAS-No.</u>
TOLUENE	108-88-3

International Regulations: As follows -**CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date: 1/22/2021 **Supersedes Date:** 11/23/2020

Reason for revision: Revision Description Changed
Product Composition Changed
Substance and/or Product Properties Changed in Section(s):
01 - Product Information
08 - Exposure Controls/Personal Protection
09 - Physical & Chemical Information
16 - Other Information
Substance Hazard Threshold % Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health:	2	Flammability:	3	Reactivity:	0	Personal Protection:	X
----------------	---	----------------------	---	--------------------	---	-----------------------------	---

Volatile Organic Compounds, gr/ltr: 389

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H320	Causes eye irritation.
H331	Toxic if inhaled.

H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:

GHS06



GHS07



GHS08



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information