



**Description:** Coated-Moisture Resistant Drop-on Glass Beads for Traffic Paints

**Product Code:** PX-118

**Applicable Specification:** Fed. Spec. TT-B-1325D Type I, Grad. A / AASHTO M 247 Type I

**Typical Uses:** Reflectorizing Liquid Air-Dry Traffic Safety Paints

**Application Rate:** 7-8 Lbs. per 100 square feet of painted surface

**Packaging:** 50 Lb. Paper Bags

**Typical Properties:**

|                            | <u>Min.</u> | <u>Max.</u> |
|----------------------------|-------------|-------------|
| <b>Roundness</b>           | 80%         | N/A         |
| <b>Index of Refraction</b> | 1.50        | 1.55        |
| <b>Specific Gravity</b>    | 2.30        | 2.50        |

## Gradation, % by Weight Passing

| <u>U.S. Sieve Number</u> |     |     |
|--------------------------|-----|-----|
| 20                       | 100 | N/A |
| 30                       | 80  | 100 |
| 50                       | 18  | 35  |
| 100                      | 0   | 10  |
| 200                      | 0   | 2   |

The Product data offered herein are, to the best of our knowledge, true and accurate, but all recommendations are made without warranty, express or implied. Since the conditions of use are beyond our control, neither Aexcel Corporation, nor its agents shall be liable for any injury, loss or damage, direct or consequential, arising from the use or the inability to use the product described herein. No person is authorized to make any statement or recommendation not contained in the Product Data, and any such statement or recommendation, if made, shall not bind the Corporation. Further, nothing contained herein shall be construed as a recommendation to use any product in conflict with existing patents, and no license under the claims of any patent is either implied or granted.