

# Safety Data Sheet



according to OSHA Hazard Communication  
29 CFR Part 1910.1200

## Section 1. Identification

**Product Information:** 12W-D195

**Product Name:** REGULAR DRY WHITE ZONE MARKING PAINT

**Recommended Use:** Liquid Paint

**Application Method:** See Product Data Sheet

**Supplied by:** Aexcel Corporation  
7373 Production Drive.  
Mentor, OH 44060

**Emergency Telephone:** Chemtrec: 800-424-9300

**Safety Data Sheet Coordinator:** IWebb@AexcelCorp.com

## Section 2. Hazard(s) identification

**EMERGENCY OVERVIEW:** Flammable liquid and vapor.

### GHS Classification

Acute Tox. 4 Inhalation, Asp. Tox. 1, Carc. 1B, Eye Irrit. 2B, Flam. Liq. 2, Muta. 1B, Skin Irrit. 2, STOT RE 2, STOT SE 3 NE

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

1% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

|  |      |  |
|--|------|--|
| Eye Irritation, category 2B            | H320 | Causes eye irritation.   |
| STOT, repeated exposure, category 2    | H373 | May cause damage to organs through prolonged or repeated exposure. |
| STOT, single exposure, category 3, NE  | H336 | May cause drowsiness or dizziness.                                 |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled.  |
| Skin Irritation, category 2            | H315 | Causes skin irritation.  |
| Flammable Liquid, category 2           | H225 | Highly flammable liquid and vapour.                                |
| Aspiration Hazard, category 1          | H304 | May be fatal if swallowed and enters airways.                      |
| Carcinogenicity, category 1B           | H350 | May cause cancer.  |
| Germ Cell Mutagenicity, category 1B    | H340 | May cause genetic defects .  |

### GHS LABEL PRECAUTIONARY STATEMENTS

|      |   |
|------|---|
| P501 | Dispose of contents/container in accordance with local rules and regulations. |
| P405 | Store locked up.  |
| P331 | Do NOT induce vomiting.   |
| P321 | Specific treatment (see on this label).                                       |
| P281 | Use personal protective equipment as required.                                |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection.    |
| P271 | Use only outdoors or in a well-ventilated area.                               |
| P264 | Wash thoroughly after handling.   |

|                |  |
|----------------|--|
| P210           | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.                                   |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.   |
| P370+P378      | In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.  |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.                              |
| P302+P352      | IF ON SKIN: Wash with plenty of water.   |
| P312           | Call a POISON CENTER/doctor if you feel unwell.  |
| P260           | Do not breathe dust/fume/gas/mist/vapours/spray.   |
| P201           | Obtain special instructions before use.  |
| P403+P235      | Store in a well-ventilated place. Keep cool.   |
| P301+P310      | IF SWALLOWED: Immediately call a POISON CENTER/doctor.   |
| P337+P313      | If eye irritation persists: Get medical advice/attention.  |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.   |
| P308+P313      | IF exposed or concerned: Get medical advice/attention.   |

**GHS SDS PRECAUTIONARY STATEMENTS**

|      |  |
|------|--|
| P243 | Take precautionary measures against static discharge.          |
| P242 | Use only non-sparking tools.                                   |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| P240 | Ground/bond container and receiving equipment.                 |
| P363 | Wash contaminated clothing before reuse.                       |

**Section 3. Composition/Information on ingredients**

| <u>Chemical Name</u>           | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u>      | <u>GHS Statements</u>                |
|--------------------------------|----------------|--------------|-------------------------|--------------------------------------|
| ALIPHATIC PETROLEUM DISTILATES | 8032-32-4      | 10-25        | GHS07-GHS08             | H304-315-320-332-336-340-350         |
| N-HEXANE 100%                  | 110-54-3       | 1.0-2.5      | GHS02-GHS07-GHS08       | H225-304-315-320-336-361-372         |
| METHANOL                       | 67-56-1        | 0.1-1.0      | GHS02-GHS06-GHS08       | H225-301-311-331-360-370             |
| METHYL ETHYL KETOXIME          | 96-29-7        | 0.1-1.0      | GHS05-GHS06-GHS07-GHS08 | H301-312-315-317-318-336-350-370-373 |
| ETHYL BENZENE                  | 100-41-4       | 0.1-1.0      | GHS02-GHS07-GHS08       | H225-304-332-340-350-373             |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**Section 4. First-aid measures**

**FIRST AID - INHALATION:** Move to fresh air. Oxygen or artificial respiration if needed.

**FIRST AID - SKIN CONTACT:** Wash off with soap and water.

**FIRST AID - EYE CONTACT:** Flush eye(s) immediately with plenty of water. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Rinse with plenty of water.

**FIRST AID - INGESTION:** Call a physician or Poison Control Center immediately. Do not induce vomiting without medical advice.

**Section 5. Fire-fighting measures**

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** May be ignited by open flame. Remove all sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Please refer to guidance NFPA 77, Recommended Practice on Static Electricity (2007); API Recommended Practice 2003, Protection Against Ignitions Arising Out of Static, Lightning, And Stray Currents (2008). Vapors are heavier than air and may spread along floors.

**SPECIAL FIREFIGHTING PROCEDURES:** Evacuate personnel to safe areas. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

## Section 6. Accidental release measures

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 7. Handling and storage



**HANDLING:** All metal parts of the mixing and processing equipment must be grounded. Handle in accordance with good industrial hygiene and safety practice. Hazardous fumes can also occur in post-processing operations. Containers of this material may be hazardous when emptied.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

## Section 8. Exposure controls/personal protection

### Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u>           | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|--------------------------------|----------------------|-----------------------|---------------------|-------------------------|
| ALIPHATIC PETROLEUM DISTILATES | 300                  | 400                   | 300                 | NE                      |
| N-HEXANE 100%                  | 50                   | 50                    | NE                  | N.E.                    |
| METHANOL                       | 200 ppm              | 250 ppm               | 200 ppm             | NE                      |
| METHYL ETHYL KETOXIME          | NE                   | NE                    | NE                  | NE                      |
| ETHYL BENZENE                  | 100 ppm              | 125 ppm               | 100 ppm             | NE                      |

**Further Advice:** MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** In case of insufficient ventilation, wear suitable respiratory equipment.



**SKIN PROTECTION:** Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** Impervious clothing.



**HYGIENIC PRACTICES:** General industrial hygiene practice. It is good practice in industrial hygiene to avoid contact with solvents by using appropriate protective measures whenever possible.

## Section 9. Physical and Chemical Properties

|                                |                |                          |            |
|--------------------------------|----------------|--------------------------|------------|
| <b>Boiling Range (F):</b>      | 149 - 306      | <b>Vapor Density:</b>    | 3.80       |
| <b>Odor:</b>                   | Characteristic | <b>Odor Threshold:</b>   | NE         |
| <b>Appearance:</b>             | Heavy Liquid   | <b>Evaporation Rate:</b> | 9.00       |
| <b>Solubility in Water:</b>    | NE             | <b>Specific Gravity:</b> | 1.526      |
| <b>Freeze Point:</b>           | NE             | <b>pH:</b>               | NE         |
| <b>Vapor Pressure (mm Hg):</b> | 59.20          | <b>Viscosity:</b>        | NE         |
| <b>Physical State:</b>         | Liquid         | <b>Flash Point, °C:</b>  | 7, °F 44.6 |

(See section 16 for abbreviation legend)

| <u>CHEMICAL NAME</u>           | <u>VAPOR DENSITY</u> | <u>EVAPORATION RATE</u> | <u>BOILING POINT</u> | <u>VP mmHg</u> | <u>at DEG. F</u> |
|--------------------------------|----------------------|-------------------------|----------------------|----------------|------------------|
| ALIPHATIC PETROLEUM DISTILATES | 3.80                 | 2.00                    | 240                  | 10.20          | 68               |
| N-HEXANE 100%                  | 3.00                 | 9.00                    | 159                  | 59.20          | 68               |
| METHANOL                       | 1.10                 | 4.10                    | 149                  | 96.0           | 68               |
| METHYL ETHYL KETOXIME          | 3.00                 | >1                      | 306                  | 2.0            | 77               |
| ETHYL BENZENE                  | 3.70                 | 0.70                    | 277                  | 9.98           | 68               |

## Section 10. Stability and reactivity

**STABILITY:** Stable under normal conditions. Stable if used as directed.

**CONDITIONS TO AVOID:** Avoid contact with skin, eyes and clothing. Do not breathe vapours or spray mist.

**INCOMPATIBILITY:** Keep away from strong oxidizing agents, heat and open flames.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide, Carbon Dioxide

## Section 11. Toxicological information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Direct skin contact may cause irritation. Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Direct eye contact may cause irritation. Mild eye irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful: may cause lung damage if swallowed. Harmful: possible risk of irreversible effects if swallowed. May be fatal or cause blindness.

**CARCINOGENICITY:** No Information

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Name according to EEC</u>   | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|--------------------------------|------------------|--------------------|-------------------|
| 8032-32-4      | ALIPHATIC PETROLEUM DISTILATES | N.I.             | N.I.               | N.I.              |
| 110-54-3       | N-HEXANE 100%                  | N.I.             | N.I.               | N.I.              |
| 67-56-1        | METHANOL                       | N.I.             | N.I.               | N.I.              |
| 96-29-7        | METHYL ETHYL KETOXIME          | N.I.             | N.I.               | N.I.              |
| 100-41-4       | ETHYL BENZENE                  | 3500             | 17800              | N.I.              |

N.I. - No Information

## Section 12. Ecological information

**ECOLOGICAL INFORMATION:** Do not allow material to contaminate ground water system. Do not contaminate ponds, waterways or ditches with chemical or used container.

## Section 13. Disposal considerations



Product

**DISPOSAL METHOD:** Contact waste disposal services. Do not flush into surface water or sanitary sewer system. Dispose of in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 14. Transport information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

|                           |                         |                   |                |
|---------------------------|-------------------------|-------------------|----------------|
| DOT Proper Shipping Name: | Paint, Flammable Liquid | Packing Group:    | II             |
| DOT Technical Name:       | Paint                   | Hazard SubClass:  | No Information |
| DOT Hazard Class:         | 3                       | Resp. Guide Page: | 128            |
| DOT UN/NA Number:         | 1263                    |                   |                |

## Section 15. Regulatory information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Specific target organ toxicity (single or repeated exposure), Aspiration Hazard, Germ cell mutagenicity

#### SARA SECTION 312:

| <u>Chemical Name</u>           | <u>CAS-No.</u> |
|--------------------------------|----------------|
| ALIPHATIC PETROLEUM DISTILATES | 8032-32-4      |
| N-HEXANE 100%                  | 110-54-3       |
| METHANOL                       | 67-56-1        |
| ETHYL BENZENE                  | 100-41-4       |

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>       | <u>CAS-No.</u> |
|----------------------------|----------------|
| N-HEXANE 100%              | 110-54-3       |
| METHANOL                   | 67-56-1        |
| ETHYL BENZENE              | 100-41-4       |
| m-XYLENE                   | 108-38-3       |
| CYCLOHEXANE                | 110-82-7       |
| p-XYLENE                   | 106-42-3       |
| o-XYLENE                   | 95-47-6        |
| SOLIDS COBALT 12%          | 136-52-7       |
| N-BUTANOL                  | 71-36-3        |
| 2-(2-BUTOXYETHOXY) ETHANOL | 112-34-5       |
| TOLUENE                    | 108-88-3       |

**TOXIC SUBSTANCES CONTROL ACT:**

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

**U.S. State Regulations:****NEW JERSEY RIGHT-TO-KNOW:**

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u>        | <u>CAS-No.</u> |
|-----------------------------|----------------|
| CALCIUM CARBONATE           | 1317-65-3      |
| MED OIL-SOY-VM&P-(Z-Z2)-RCI | 68082-51-9     |
| MAGNESIUM SILICATE HYDRATE  | 14807-96-6     |

**PENNSYLVANIA RIGHT-TO-KNOW**

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u>                | <u>CAS-No.</u> |
|-------------------------------------|----------------|
| CALCIUM CARBONATE                   | 1317-65-3      |
| MED OIL-SOY-VM&P-(Z-Z2)-RCI         | 68082-51-9     |
| MAGNESIUM SILICATE HYDRATE          | 14807-96-6     |
| WOLLASTONITE (CALCIUM METASILICATE) | 13983-17-0     |
| TITANIUM DIOXIDE                    | 13463-67-7     |

**CALIFORNIA PROPOSITION 65 CARCINOGENS****WARNING**

The following ingredients present in the product are known to the state of California to cause Cancer:

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| TITANIUM DIOXIDE     | 13463-67-7     |
| ETHYL BENZENE        | 100-41-4       |

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

| <u>Chemical Name</u> | <u>CAS-No.</u> |
|----------------------|----------------|
| METHANOL             | 67-56-1        |
| TOLUENE              | 108-88-3       |

**International Regulations: As follows -****CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

**WHMIS Class:** No Information

**Section 16. Other information, including date of preparation of the last revision**

**Revision Date:** 6/10/2026 **Supersedes Date:** 4/17/2024

**Reason for revision:** Product Composition Changed  
 Substance and/or Product Properties Changed in Section(s):  
 02 - Hazards Identification  
 15 - Regulatory Information  
 Substance Hazard Threshold % Changed  
 Substance CAS Number Changed  
 Substance Regulatory CAS Number Changed  
 Substance Chemical Name Changed  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

|                |   |                      |   |                    |   |                             |   |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|
| <b>Health:</b> | 2 | <b>Flammability:</b> | 3 | <b>Reactivity:</b> | 0 | <b>Personal Protection:</b> | X |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|

**Volatile Organic Compounds, gr/ltr:** 354

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.  |
| H301 | Toxic if swallowed.  |
| H304 | May be fatal if swallowed and enters airways.  |
| H311 | Toxic in contact with skin.  |
| H312 | Harmful in contact with skin.  |
| H315 | Causes skin irritation.  |
| H317 | May cause an allergic skin reaction.   |
| H318 | Causes serious eye damage.   |
| H320 | Causes eye irritation.   |
| H331 | Toxic if inhaled.  |
| H332 | Harmful if inhaled.  |
| H336 | May cause drowsiness or dizziness.   |
| H340 | May cause genetic defects.   |
| H350 | May cause cancer   |
| H360 | May damage fertility or the unborn child.  |
| H361 | Suspected of damaging fertility or the unborn child.   |
| H370 | Causes damage to organs . Classified Category 1 Substances that produced significant toxicity in humans and evidence to produce significant toxicity with single exposure. Cell death, adverse change in biochemistry, haematology or urinalysis parameters, Central or peripheral nervous system and effects senses. multifocal or diffuse necrosis, fibrosis or granuloma formation in organs. |
| H372 | Causes damage to organs through prolonged or repeated exposure.  |
| H373 | May cause damage to organs through prolonged or repeated exposure.   |

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



GHS05



GHS06



GHS07



**GHS08**



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information