Safety Data Sheet



according to OSHA Hazard Communication 29 CFR Part 1910.1200

Section 1. Identification

Product Information: 25W-G022

Product Name: WHITE MMA 98:2 PROFILE

Recommended Use: Liquid Paint

Application Method: See Product Data Sheet

Supplied by: **Aexcel Corporation**

7373 Production Drive.

Mentor, OH 44060

Emergency Telephone: Chemtrec: 800-424-9300 Safety Data Sheet Coordinator: IWebb@AexcelCorp.com

Section 2. Hazard(s) identification

EMERGENCY OVERVIEW: Flammable liquid and vapor.

GHS Classification

Flam. Liq. 1, Repr. 2, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI

Symbol(s) of Product







Signal Word

Danger

Possible Hazards

26% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Flammable Liquid, category 1 H224 Extremely flammable liquid and vapour.

Reproductive Toxicity, category 2 H361 Suspected of damaging fertility or the unborn child.

STOT, single exposure, category 3, RTI H335 May cause respiratory irritation.

Skin Irritation, category 2 H315 Causes skin irritation.

Skin Sensitizer, category 1 H317 May cause an allergic skin reaction.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No

smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P302+P352 IF ON SKIN: Wash with plenty of water.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER/doctor if you feel unwell.

P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P370+P378 In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P403+P235 Store in a well-ventilated place. Keep cool.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local rules and regulations.

GHS SDS PRECAUTIONARY STATEMENTS

P240 Ground/bond container and receiving equipment.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P363 Wash contaminated clothing before reuse.

Section 3. Composition/Information on ingredients

Chemical Name	CAS-No.	Wt. %	GHS Symbols	GHS Statements
METHYL METHACRYLATE	80-62-6	10-25	GHS02-GHS07	H225-315-317-335
2-ETHYLHEXYL ACRYLATE	103-11-7	2.5-10	GHS07	H315-317-335
TITANIUM DIOXIDE	13463-67-7	2.5-10	GHS06-GHS08	H331-361

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

Section 4. First-aid measures



FIRST AID - INHALATION: Move to fresh air.

FIRST AID - SKIN CONTACT: Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

FIRST AID - EYE CONTACT: In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

FIRST AID - INGESTION: Call a physician immediately. Do not induce vomiting without medical advice.

Section 5. Fire-fighting measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Remove all sources of ignition.

SPECIAL FIREFIGHTING PROCEDURES: Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

Section 6. Accidental release measures

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 7. Handling and storage





HANDLING: Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

STORAGE: Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

Section 8. Exposure controls/personal protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u>	ACGIH TLV-TWA	ACGIH-TLV STEL	OSHA PEL-TWA	OSHA PEL-CEILING
METHYL METHACRYLATE	50	100	100	NE
2-ETHYLHEXYL ACRYLATE	3 mg/m3	NE	NE	NE
TITANIUM DIOXIDE	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



SKIN PROTECTION: Impervious gloves.



EYE PROTECTION: Safety glasses with side-shields.



OTHER PROTECTIVE EQUIPMENT: Impervious clothing.



HYGIENIC PRACTICES: General industrial hygiene practice. Remove and wash contaminated clothing before re-use.

Section 9. Physical and Chemical Properties

Boiling Range: 0 - 0Vapor Density: 6.40 Odor: Characteristic Odor Threshold: NE Heavy White Liquid **Evaporation Rate:** 3.10 Appearance: Solubility in Water: Specific Gravity: 1.990 NF Freeze Point: No Information pH: NE Vapor Pressure: 40.00 Viscosity: NE Flash Point, °C: 10, °F 50 **Physical State:** Liquid

(See section 16 for abbreviation legend)

CHEMICAL NAMEVAPOR DENSITYEVAPORATION RATEBOILING POINTVP mmHgat DEG. FMETHYL METHACRYLATE3.603.1021240.0068

2-ETHYLHEXYL 6.40 NA 419 0.20 68

TITANIUM DIOXIDE NE NE 0 NE NE NE

Section 10. Stability and reactivity

STABILITY: Stable under normal conditions. Stable if used as directed.

CONDITIONS TO AVOID: Avoid contact with skin, eyes and clothing.

INCOMPATIBILITY: Strong oxidizing agents. Keep away from strong oxidizing agents, heat and open flames.

HAZARDOUS DECOMPOSITION PRODUCTS: No decomposition if stored and applied as directed.

Section 11. Toxicological information



Practical Experiences

EFFECT OF OVEREXPOSURE - INHALATION: Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation.

EFFECT OF OVEREXPOSURE - INGESTION: Harmful: may cause lung damage if swallowed. Harmful if swallowed.

CARCINOGENICITY: No Information

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Name according to EEC	Oral LD50	Dermal LD50	Vapor LC50
80-62-6	METHYL METHACRYLATE	N.I.	N.I.	N.I.
103-11-7	2-ETHYLHEXYL ACRYLATE	N.I.	N.I.	N.I.
13463-67-7	TITANIUM DIOXIDE	10000	10000	6.80

N.I. - No Information

Section 12. Ecological information

ECOLOGICAL INFORMATION: Do not contaminate ponds, waterways or ditches with chemical or used container.

Section 13. Disposal considerations



Product

DISPOSAL METHOD: Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Soak up with inert absorbent material and dispose of as hazardous waste.

Section 14. Transport information

SPECIAL TRANSPORT PRECAUTIONS: No Information

Packing Group:

DOT Proper Shipping Paint, Flammable Liquid

DOT Technical Name: Paint Hazard SubClass: No Information

DOT Hazard Class: 3 Resp. Guide Page: 128

DOT UN/NA Number: 1263

Section 15. Regulatory information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 312:

<u>Chemical Name</u>	CAS-No.
METHYL METHACRYLATE	80-62-6
2-ETHYLHEXYL ACRYLATE	103-11-7

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	<u>CAS-No.</u>
METHYL METHACRYLATE	80-62-6
1-METHYL-2-PYRROLIDONE	872-50-4
XYLENE (100%)	1330-20-7
ETHYL BENZENE	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

U.S. State Regulations:

NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
AASHTO TYPE I, UNCOATED BEADS	MIXTURE
AGGREGATE	MIXTURE
LIMESTONE	1317-65-3

PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
AASHTO TYPE I, UNCOATED BEADS	MIXTURE
AGGREGATE	MIXTURE
LIMESTONE	1317-65-3

CALIFORNIA PROPOSITION 65 CARCINOGENS



The following ingredients present in the product are known to the state of California to cause Cancer:

Chemical NameCAS-No.TITANIUM DIOXIDE13463-67-7N,N-DIMETHYL-P-TOLUIDINE99-97-8ETHYL BENZENE100-41-4

CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

Chemical NameCAS-No.1-METHYL-2-PYRROLIDONE872-50-4

International Regulations: As follows -

CANADIAN WHMIS:

All components of this material are listed on the Domestic Substance List.

WHMIS Class: No Information

Section 16. Other information, including date of preparation of the last revision

Revision Date: 4/23/2021 Supercedes Date: 8/27/2015

Reason for revision: Revision Description Changed

Product Composition Changed

Substance and/or Product Properties Changed in Section(s):

01 - Product Information05 - Flammability Information

09 - Physical & Chemical Information

15 - Regulatory Information16 - Other Information

Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health: 2 Flammability: 3 Reactivity: 2 Personal Protection: X

Volatile Organic Compounds, gr/ltr: 11

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H225 Highly flammable liquid and vapour.

H315 Causes skin irritation.


H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H335 May cause respiratory irritation.

H361 Suspected of damaging fertility or the unborn child.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information