

# Safety Data Sheet



according to OSHA Hazard Communication  
29 CFR Part 1910.1200

## Section 1. Identification

**Product Information:** 25Y-G014

**Product Name:** YELLOW 4:1 EXTRUDE-TYPE P & III & ALASKA

**Recommended Use:** Liquid Paint

**Application Method:** See Product Data Sheet

**Supplied by:** Aexcel Corporation  
7373 Production Drive.  
Mentor, OH 44060

**Emergency Telephone:** Chemtrec: 800-424-9300

**Safety Data Sheet Coordinator:** IWebb@AexcelCorp.com

## Section 2. Hazard(s) identification

**EMERGENCY OVERVIEW:** Flammable liquid and vapor.

### GHS Classification

Flam. Liq. 1, Skin Irrit. 2, Skin Sens. 1, STOT SE 3 RTI

### Symbol(s) of Product



### Signal Word

Danger

### Possible Hazards

26% of the mixture consists of ingredients of unknown acute toxicity

### GHS HAZARD STATEMENTS

|  |      |  |
|--|------|--|
| Flammable Liquid, category 1           | H224 | Extremely flammable liquid and vapour. |
| STOT, single exposure, category 3, RTI | H335 | May cause respiratory irritation.      |
| Skin Irritation, category 2            | H315 | Causes skin irritation.                |
| Skin Sensitizer, category 1            | H317 | May cause an allergic skin reaction.   |

### GHS LABEL PRECAUTIONARY STATEMENTS

|           |  |
|-----------|--|
| P210      | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P261      | Avoid breathing dust/fume/gas/mist/vapours/spray.  |
| P264      | Wash thoroughly after handling.  |
| P271      | Use only outdoors or in a well-ventilated area.  |
| P272      | Contaminated work clothing should not be allowed out of the workplace.                         |
| P280      | Wear protective gloves/protective clothing/eye protection/face protection.                     |
| P302+P352 | IF ON SKIN: Wash with plenty of water.   |

|                |   |
|----------------|---|
| P303+P361+P353 | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. |
| P304+P340      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.                          |
| P312           | Call a POISON CENTER/doctor if you feel unwell.   |
| P321           | Specific treatment (see on this label).   |
| P332+P313      | If skin irritation occurs: Get medical advice/attention.  |
| P333+P313      | If skin irritation or rash occurs: Get medical advice/attention.                                    |
| P370+P378      | In case of fire: Use dry chemical, carbon dioxide, or foam to extinguish.                           |
| P403+P233      | Store in a well-ventilated place. Keep container tightly closed.                                    |
| P403+P235      | Store in a well-ventilated place. Keep cool.  |
| P405           | Store locked up.  |
| P501           | Dispose of contents/container in accordance with local rules and regulations.                       |

**GHS SDS PRECAUTIONARY STATEMENTS**

|      |  |
|------|--|
| P240 | Ground/bond container and receiving equipment.                 |
| P241 | Use explosion-proof electrical/ventilating/lighting/equipment. |
| P242 | Use only non-sparking tools.                                   |
| P243 | Take precautionary measures against static discharge.          |
| P363 | Wash contaminated clothing before reuse.                       |

**Section 3. Composition/Information on ingredients**

| <u>Chemical Name</u>  | <u>CAS-No.</u> | <u>Wt. %</u> | <u>GHS Symbols</u> | <u>GHS Statements</u> |
|-----------------------|----------------|--------------|--------------------|-----------------------|
| METHYL METHACRYLATE   | 80-62-6        | 10-25        | GHS02-GHS07        | H225-315-317-335      |
| 2-ETHYLHEXYL ACRYLATE | 103-11-7       | 10-25        | GHS07              | H315-317-335          |
| TITANIUM DIOXIDE      | 13463-67-7     | 1.0-2.5      | GHS06-GHS08        | H331-361              |

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

**Section 4. First-aid measures**

**FIRST AID - INHALATION:** Move to fresh air.

**FIRST AID - SKIN CONTACT:** Wash off immediately with soap and plenty of water removing all contaminated clothes and shoes.

**FIRST AID - EYE CONTACT:** In the case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Rinse with plenty of water.

**FIRST AID - INGESTION:** Call a physician immediately. Do not induce vomiting without medical advice.

**Section 5. Fire-fighting measures**

**UNUSUAL FIRE AND EXPLOSION HAZARDS:** Remove all sources of ignition.

**SPECIAL FIREFIGHTING PROCEDURES:** Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

**EXTINGUISHING MEDIA:** Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam

**Section 6. Accidental release measures**

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 7. Handling and storage



**HANDLING:** Containers of this material may be hazardous when emptied. Handle in accordance with good industrial hygiene and safety practice.

**STORAGE:** Harmful - Store away from foodstuffs. Keep containers tightly closed. Keep in a well-ventilated place. Keep locked-up. For Industrial Use Only

## Section 8. Exposure controls/personal protection

### Ingredients with Occupational Exposure Limits

| <u>Chemical Name</u>  | <u>ACGIH TLV-TWA</u> | <u>ACGIH-TLV STEL</u> | <u>OSHA PEL-TWA</u> | <u>OSHA PEL-CEILING</u> |
|-----------------------|----------------------|-----------------------|---------------------|-------------------------|
| METHYL METHACRYLATE   | 50                   | 100                   | 100                 | NE                      |
| 2-ETHYLHEXYL ACRYLATE | 3 mg/m <sup>3</sup>  | NE                    | NE                  | NE                      |
| TITANIUM DIOXIDE      | N.E.                 | N.E.                  | N.E.                | N.E.                    |

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation  
Sk = Skin Sensitizer N.E. = Not Established

### Personal Protection



**RESPIRATORY PROTECTION:** In the case of respirable dust and/or fumes, use self-contained breathing apparatus.



**SKIN PROTECTION:** Impervious gloves.



**EYE PROTECTION:** Safety glasses with side-shields.



**OTHER PROTECTIVE EQUIPMENT:** Impervious clothing.



**HYGIENIC PRACTICES:** General industrial hygiene practice. Remove and wash contaminated clothing before re-use.

## Section 9. Physical and Chemical Properties

|                             |                     |                          |           |
|-----------------------------|---------------------|--------------------------|-----------|
| <b>Boiling Range:</b>       | 0 - 0               | <b>Vapor Density:</b>    | 3.60      |
| <b>Odor:</b>                | Characteristic      | <b>Odor Threshold:</b>   | NE        |
| <b>Appearance:</b>          | Heavy Yellow Liquid | <b>Evaporation Rate:</b> | 3.10      |
| <b>Solubility in Water:</b> | NE                  | <b>Specific Gravity:</b> | 1.806     |
| <b>Freeze Point:</b>        | NE                  | <b>pH:</b>               | NE        |
| <b>Vapor Pressure:</b>      | 40.00               | <b>Viscosity:</b>        | NE        |
| <b>Physical State:</b>      | Liquid              | <b>Flash Point, °C:</b>  | 10, °F 50 |

(See section 16 for abbreviation legend)

| <u>CHEMICAL NAME</u> | <u>VAPOR DENSITY</u> | <u>EVAPORATION RATE</u> | <u>BOILING POINT</u> | <u>VP mmHg</u> | <u>at DEG. F</u> |
|----------------------|----------------------|-------------------------|----------------------|----------------|------------------|
| METHYL METHACRYLATE  | 3.60                 | 3.10                    | 212                  | 40.00          | 68               |

|                          |      |    |     |      |    |
|--------------------------|------|----|-----|------|----|
| 2-ETHYLHEXYL<br>ACRYLATE | 6.40 | NA | 419 | 0.20 | 68 |
| TITANIUM DIOXIDE         | NE   | NE | 0   | NE   | NE |

## Section 10. Stability and reactivity

**STABILITY:** Stable under normal conditions. Stable if used as directed.

**CONDITIONS TO AVOID:** Avoid contact with skin, eyes and clothing.

**INCOMPATIBILITY:** Strong oxidizing agents. Keep away from strong oxidizing agents, heat and open flames.

**HAZARDOUS DECOMPOSITION PRODUCTS:** No decomposition if stored and applied as directed.

## Section 11. Toxicological information



### Practical Experiences

**EFFECT OF OVEREXPOSURE - INHALATION:** Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes).

**EFFECT OF OVEREXPOSURE - SKIN CONTACT:** Local ventilation of emission sources may be necessary to maintain ambient concentrations below recommended exposure limits.

**EFFECT OF OVEREXPOSURE - EYE CONTACT:** Direct eye contact may cause irritation.

**EFFECT OF OVEREXPOSURE - INGESTION:** Harmful: may cause lung damage if swallowed. Harmful if swallowed.

**CARCINOGENICITY:** No Information

### Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below:

| <u>CAS-No.</u> | <u>Name according to EEC</u> | <u>Oral LD50</u> | <u>Dermal LD50</u> | <u>Vapor LC50</u> |
|----------------|------------------------------|------------------|--------------------|-------------------|
| 80-62-6        | METHYL METHACRYLATE          | N.I.             | N.I.               | N.I.              |
| 103-11-7       | 2-ETHYLHEXYL ACRYLATE        | N.I.             | N.I.               | N.I.              |
| 13463-67-7     | TITANIUM DIOXIDE             | 10000            | 10000              | 6.80              |

N.I. - No Information

## Section 12. Ecological information

**ECOLOGICAL INFORMATION:** Do not contaminate ponds, waterways or ditches with chemical or used container.

## Section 13. Disposal considerations



### Product

**DISPOSAL METHOD:** Contact waste disposal services. Dispose of in accordance with all local, state and federal regulations.

**STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:** Soak up with inert absorbent material and dispose of as hazardous waste.

## Section 14. Transport information

**SPECIAL TRANSPORT PRECAUTIONS:** No Information

DOT Proper Shipping      Paint, Flammable Liquid  
 DOT Technical Name:      Paint  
 DOT Hazard Class:        3  
 DOT UN/NA Number:      1263

Packing Group:            II  
 Hazard SubClass:        No Information  
 Resp. Guide Page:        128

## Section 15. Regulatory information

### U.S. Federal Regulations:

#### CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

#### SARA SECTION 312:

| <u>Chemical Name</u>  | <u>CAS-No.</u> |
|-----------------------|----------------|
| METHYL METHACRYLATE   | 80-62-6        |
| 2-ETHYLHEXYL ACRYLATE | 103-11-7       |

#### SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

| <u>Chemical Name</u>   | <u>CAS-No.</u> |
|------------------------|----------------|
| METHYL METHACRYLATE    | 80-62-6        |
| 1-METHYL-2-PYRROLIDONE | 872-50-4       |

#### TOXIC SUBSTANCES CONTROL ACT:

All components of this material are listed on the US Toxic Substance Control Act (TSCA inventory).

### U.S. State Regulations:

#### NEW JERSEY RIGHT-TO-KNOW:

The following materials are non-hazardous, but are among the top five components in this product.

| <u>Chemical Name</u>          | <u>CAS-No.</u> |
|-------------------------------|----------------|
| LIMESTONE                     | 1317-65-3      |
| AASHTO TYPE I, UNCOATED BEADS | MIXTURE        |
| AGGREGATE                     | MIXTURE        |

#### PENNSYLVANIA RIGHT-TO-KNOW

The following non-hazardous ingredients are present in the product at greater than 3%.

| <u>Chemical Name</u>          | <u>CAS-No.</u> |
|-------------------------------|----------------|
| LIMESTONE                     | 1317-65-3      |
| AASHTO TYPE I, UNCOATED BEADS | MIXTURE        |
| AGGREGATE                     | MIXTURE        |
| YELLOW 65                     | 6528-34-3      |

**CALIFORNIA PROPOSITION 65 CARCINOGENS**

The following ingredients present in the product are known to the state of California to cause Cancer:

| <u>Chemical Name</u>     | <u>CAS-No.</u> |
|--------------------------|----------------|
| TITANIUM DIOXIDE         | 13463-67-7     |
| N,N-DIMETHYL-P-TOLUIDINE | 99-97-8        |

**CALIFORNIA PROPOSITION 65 REPRODUCTIVE TOXINS**

The following ingredients present in the product are known to the state of California to cause birth defects, or other reproductive hazards.

| <u>Chemical Name</u>   | <u>CAS-No.</u> |
|------------------------|----------------|
| 1-METHYL-2-PYRROLIDONE | 872-50-4       |

**International Regulations: As follows -****CANADIAN WHMIS:**

All components of this material are listed on the Domestic Substance List.

**WHMIS Class:** No Information

**Section 16. Other information, including date of preparation of the last revision**

**Revision Date:** 4/23/2021 **Supersedes Date:** 4/24/2020

**Reason for revision:** Product Composition Changed  
 Substance and/or Product Properties Changed in Section(s):  
 01 - Product Information  
 05 - Flammability Information  
 15 - Regulatory Information  
 Revision Statement(s) Changed

**Datasheet produced by:** Regulatory Department

**HMIS Ratings:**

|                |   |                      |   |                    |   |                             |   |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|
| <b>Health:</b> | 2 | <b>Flammability:</b> | 3 | <b>Reactivity:</b> | 2 | <b>Personal Protection:</b> | X |
|----------------|---|----------------------|---|--------------------|---|-----------------------------|---|

**Volatile Organic Compounds, gr/ltr:** 6

**Text for GHS Hazard Statements shown in Section 3 describing each ingredient:**

|      |  |
|------|--|
| H225 | Highly flammable liquid and vapour.                  |
| H315 | Causes skin irritation.                              |
| H317 | May cause an allergic skin reaction.                 |
| H331 | Toxic if inhaled.                                    |
| H335 | May cause respiratory irritation.                    |
| H361 | Suspected of damaging fertility or the unborn child. |

**Icons for GHS Pictograms shown in Section 3 describing each ingredient:**

GHS02



**GHS06**



**GHS07**



**GHS08**



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined, N.I. - No Information

No Information